

# THOR:

BUILT TO ENGAGE



Slate 3.9



Edge 3.9i



Edge 3.4 & 3.4i



Edge 2.9 & 2.9i

## LED PANEL COMPARISONS

Pixel Pitch	3.91	3.91	3.47	2.9
Closest Viewer	15 FT / 4M	18 FT / 5M	15 FT / 4M	15 FT / 4M
Size Availability	500mm x 500mm	500mm x 500mm 500mm x 1000mm	500mm x 500mm 500mm x 1000mm	500mm x 500mm 500mm x 1000mm
Resolution	128x128	128x128 128x256	144x144 144x288	168x168 168x336
Refresh Rate	3840+ Hz S-PWM	3840+ Hz S-PWM	3840+ Hz S-PWM	3840+ Hz S-PWM
Scan Rate	1/16	1/16	1/12	1/14
Gray Scale	14 bits	14 bits	18* bits 16 bits	16 bits
Brightness	1300 nits	1300 nits	1000 nits	1000 nits
Viewing Angles	160° x 140°	140° x 140°	140° x 140°	140° x 140°
Curving Radius	NA	NA	Concave 10° Convex 10°	**NA
Receiving Card	NovaStar MRV270	NovaStar A4s	Brompton R2 NovaStar A8s	Brompton R2 NovaStar A8s
Certifications	FCC, UL, EMC	FCC, ETL, EMC	FCC, ETL, EMC	FCC, ETL, EMC
Panel Stacking				
Flown Height Max.	9M (29.5')	14M (46') 9:1 Safety Ratio	14M (46') 9:1 Safety Ratio	14M (46') 9:1 Safety Ratio
Ground Stack Max.	4.5M (15')	6M (20')	6M (20')	6M (20')
Serviceability	Front - Rear	Front - Rear	Front - Rear	Front - Rear

\*Software Emulated  
\*\*Custom order for Curve